

1M60A Air-Cooled Chiller/Heater

Specifications and Features

- Fluid Setpoint Range +4°C to +30°C
- Temperature Stability ± 1.0°C
- Net Cooling Capacities 17,500 Watts at +10°C
Ambient air up to 90°F
60,000 Btu/hr at +50°F
- Heating Capacity 3,000 Watts on 460 VAC
- Recirculating Flow/Pressure 4 Gpm at 30 PSI
- Stainless Steel Reservoir 10 Gallons
- Recirculating Fluid 35% Ethylene Glycol /
65% Water
- Recirculating Supply/
Return Fittings 3/4" Stainless Steel FNPT
- Condenser Air Flow 7,800 SCFM front to rear
- Electrical Service 440/480 VAC, 60 Hz, 3 phase,
40 amp service
- Physical Parameters 66" high x 38" wide x 62" deep
1000 lbs dry weight approx.
- Warranty 12 Months, Parts and Labor
- Refrigeration 10 Hp Scroll compressor,
- Condenser Dual Fan unit controlled to maintain ideal
head pressure over all load conditions
- Recirculation 1.0 HP centrifugal pump, rotary flowmeter
installed in fluid return circuit, output flow
adjust globe valve, panel mounted pressure
gauge, copper piping
- Safety Reservoir low level and empty switches,
Interlocks refrigerant high and low pressure
switches, fluid over temperature switch,
emergency off switch



Similar Model Shown

- Controller PID type controller with a 5.7" color
graphic touch-screen display providing
fully proportional cooling and heating
with the Mydax patented refrigeration
circuit
- Interfacing Remote contacts providing run and
alarm status, RS-232 serial interface
- Construction Welded steel frame with aluminum
panels, powder coated and mounted
on locking casters
- Safety Standards Refrigeration Standard AHRI 550/590,
National Electrical Code NFPA-70,
Electrical Standard for Industrial
Machinery NFPA-79

**Please contact Mydax to customize this
system for your specific needs**



12260 Shale Ridge Lane
Auburn, CA 95602
530-888-6662

5/19/2015

Patents: #4,742,689, #4,959,972, #4,934,155

Fax: 530-888-0962
www.mydax.com
E-mail: sales@mydax.com