

3LM30A 3-Channel Air-Cooled Chiller/Heater

Specifications and Features

- Fluid Setpoint Range -15°C to +50°C
- Temperature Stability ± 0.5°C
- Net Cooling Capacities 9,000 Watts at -15°C
Total is shared between 3 loops: 3,000 watts in any single loop
- Heating Capacity 3,000 Watts on 460 VAC
Each Loop
- Recirculating Flow/Pressure 4 Gpm at 110 PSI, Each Loop
- Stainless Steel Reservoir 5 Gallons
- Recirculating Fluid PAO, Royco 602
MIL-PRF-87252
- Recirculating Supply/
Return Fittings 3/4" Stainless Steel FNPT
- Condenser Air Flow 10,400 SCFM Upward
- Electrical Service 440/480 VAC, 60 Hz, 3 phase,
60 amp service
- Physical Parameters 81" H x 50" W x 80" D
- Warranty 12 Months, Parts and Labor
- Refrigeration 20 Hp semi-hermetically sealed compressor,
R-507 refrigerant, 50 lbs.
- Condenser Dual Fan unit controlled to maintain ideal
head pressure over the full ambient range
- Recirculation Three 2 HP seal-less canned motor turbine
pumps powered by variable frequency
drives for optimum flow and pressure adjust
ments, rotary flowmeters installed in fluid
return circuit, panel mounted pressure
gauges
- Safety Interlocks Reservoir low level and empty switches,
refrigerant high and low pressure
switches, fluid over-pressure and
over temperature switches, emergency off
switch



Similar Model Shown

- Controller PID type controller with a 5.7" color
graphic touch-screen display providing
fully proportional cooling and heating
with the Mydax patented refrigeration
circuit
- Interfacing Remote contacts providing run and
alarm status, RS-232 serial interface
for remote control and monitoring
- Construction Welded steel frame with aluminum
panels, powder coated and mounted
on locking casters
- Safety Refrigeration Standard ARI 590-2,
Standards National Electrical Code NFPA-70,
Electrical Standard for Industrial
Machinery NFPA-79

**Please contact Mydax to customize this
system for your specific needs**



12260 Shale Ridge Lane
Auburn, CA 95602
530-888-6662

2013.10.02

Patents: #4,742,689, #4,959,972, #4,934,155

Fax: 530-888-0962
www.mydax.com
E-mail: sales@mydax.com