

CryoDax 12 Water-Cooled Chiller/Heater

Standard Specifications and Features

- Fluid Setpoint Range -70°C to +80°C
- Temperature Stability ± 1.0°C
- Net Cooling Capacities 9.2 kW at -30°C
5.0 kW at -40°C 4.0 kW at -50°C
1.5 kW at -60°C 400 W at -70°C
(*Ratings on 60 Hz with standard pump)
- Nominal Heating Capacity 3,000 Watts
- Recirculating Flow/Pressure 4 Gpm at 25 PSI,
2 Gpm at 45 PSI
- Stainless Steel Reservoir 5 Gallons (vented)
- Recirculating Fluid Syltherm HF or XLT
- Recirculating Supply/
Return Fittings 3/4" Stainless Steel FNPT
- Facilities Requirements Up to 8.0 Gpm at 70°F inlet,
20 Psi ΔP
- Facilities Supply/
Return Fittings 3/4" Stainless Steel FNPT
- Electrical Service 440/480 VAC, 60 Hz, 3 phase,
30 amp service
- Physical Parameters 62" H x 36" W x 42" D,
980 lbs. dry weight approx.
- Warranty 12 Months, Parts and Labor
- Refrigeration 12 Hp semi-hermetically sealed compressor,
R-507 refrigerant
- Condenser Brazed plate heat exchanger with a
water flow control valve to automatically
maintain condensing temperature
- Recirculation 1.5 Hp SS seal-less magnetic-drive turbine
pump, turbine fluid flowmeter in recirculating
return, pressure gauge, overpressure switch,
brazed plate heat exchanger, copper piping
- Safety Interlocks Fluid low level and empty switches,
refrigerant high and low pressure switches,
fluid over-temperature switch, emergency
off switch



- Controller PID type controller with a 5.7" color
graphic touch-screen display providing
fully proportional cooling and heating
with the Mydax patented refrigeration
circuit
- Interfacing Remote contacts providing run and
alarm status, RS-232 serial interface
for remote control and monitoring
- Construction Welded steel frame with aluminum
panels, frame and panels are powder
coated for durability, mounted on
locking casters and leveling feet
- Safety Standards Refrigeration Standard AHRI 550/590,
National Electrical Code NFPA-70,
Electrical Standard for Industrial
Machinery NFPA-79

Please contact Mydax to customize this system for your specific needs



12260 Shale Ridge Lane
Auburn, CA 95602
530-888-6662

10/16/2017

Patents: #4,742,689, #4,959,972, #4,934,155

Fax: 530-888-0962
www.mydax.com
E-mail: sales@mydax.com